```
Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ npm -v
1.4.28

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ node --version
v0.10.33

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ npm install mongodb

> kerberos@0.0.18 install C:\adapt\Simons Adapt\node_modules\mongodb\node_module
                                              s\kerberos

> (node-gyp rebuild) || (exit 0)


C:\adapt\Simons Adapt\node_modules\mongodb\node_modules\kerberos>node "C:\Progra
                                          m Files\nodejs\node_modules\npm\bin
\node-gyp-bin\\..\..\node_modules\node-gyp\bi
                n\node-gyp.js" rebuild
gypmongodb@2.1.4 node_modules\mongodb
├── es6-promise@3.0.2
├── readable-stream@1.0.31 (string_decoder@0.10.31, isarray@0.0.1, inherits@2.0.
                                          1, core-util-is@1.0.2)
├── kerberos@0.0.18 (nan@2.0.9)
└── mongodb-core@1.2.32 (bson@0.4.21)

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ npm install -g grunt-cli
C:\Users\Simon\AppData\Roaming\npm\grunt -> C:\Users\Simon\AppData\Roaming\npm\n
                                          ode_modules\grunt-cli\bin\grunt
grunt-cli@0.1.13 C:\Users\Simon\AppData\Roaming\npm\node_modules\grunt-cli
├── resolve@0.3.1
├── nopt@1.0.10 (abbrev@1.0.7)
└── findup-sync@0.1.3 (lodash@2.4.2, glob@3.2.11)

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ npm install -g adapt-cli
npm WARN deprecated lodash@0.9.2: lodash@<2.0.0 is no longer maintained. Upgrade
                                          to lodash@^3.0.0
npm WARN engine cryptiles@2.0.5: wanted: {"node":">=0.10.40"} (current: {"node":
                                          "0.10.33","npm":"1.4.28"})
npm WARN engine boom@2.10.1: wanted: {"node":">=0.10.40"} (current: {"node":"0.1
                                          0.33","npm":"1.4.28"})
npm WARN engine hoek@2.16.3: wanted: {"node":">=0.10.40"} (current: {"node":"0.1
                                          0.33","npm":"1.4.28"})
npm WARN deprecated npmconf@2.1.2: this package has been reintegrated into npm a
                                          nd is now out of date with respect to npm
C:\Users\Simon\AppData\Roaming\npm\adapt -> C:\Users\Simon\AppData\Roaming\npm\n
                                          ode_modules\adapt-cli\bin\adapt
adapt-cli@2.0.2 C:\Users\Simon\AppData\Roaming\npm\node_modules\adapt-cli
├── url-join@0.0.1
├── bower-endpoint-parser@0.2.2
├── semver@4.3.6
├── q@1.4.1
├── uuid@2.0.1
```

```
├── speakingurl@1.1.5
├── debug@2.1.3 (ms@0.7.0)
├── chalk@1.0.0 (escape-string-regexp@1.0.4, ansi-styles@2.1.0, supports-color@1
                                .3.1, strip-ansi@2.0.1, has-ansi@1.0.3)
├── q-io@1.12.0 (mimeparse@0.1.4, url2@0.0.0, qs@1.2.2, mime@1.3.4, collections@
                                0.2.2)
├── grunt@0.4.5 (eventemitter2@0.4.14, lodash@0.9.2, async@0.1.22, getobject@0.1
                                .0, dateformat@1.0.2-1.2.3, rimraf@2.2.8,
which@1.0.9, colors@0.6.2, hooker@0.2.
            3, grunt-legacy-util@0.2.0, coffee-script@1.3.3, iconv-lite@0.2.11, underscore.s
                                tring@2.2.1, nopt@1.0.10, exit@0.1.2,
minimatch@0.2.14, grunt-legacy-log@0.1.3,
            glob@3.1.21, findup-sync@0.1.3, js-yaml@2.0.5)
├── prompt@0.2.14 (revalidator@0.1.8, pkginfo@0.3.1, read@1.0.7, winston@0.8.3,
                                utile@0.2.1)
├── lodash@3.6.0
├── download@0.1.18 (get-stdin@0.1.0, each-async@0.1.3, get-urls@0.1.2, mkdirp@0
                                .3.5, nopt@2.2.1, through2@0.4.2,
request@2.69.0, decompress@0.2.4)
├── bower@1.3.12 (chmodr@0.1.0, is-root@1.0.0, junk@1.0.2, stringify-object@1.0.
                                1, osenv@0.1.0, abbrev@1.0.7, which@1.0.9,
opn@1.0.2, archy@0.0.2, bower-logger@
            0.2.2, lockfile@1.0.1, rimraf@2.2.8, lru-cache@2.5.2, nopt@3.0.6, graceful-fs@3.
                                0.8, retry@0.6.0, q@1.0.1, tmp@
0.0.23, semver@2.3.2, p-throttler@0.1.0, shell-qu
            ote@1.4.3, request-progress@0.3.0, promptly@0.2.0, mkdirp@0.5.0, bower-
json@0.4.                                                            0, fstream@1.0.8,
chalk@0.5.0, fstream-ignore@1.0.3, glob@4.0.6, bower-config@0.
            5.2, request@2.42.0, cardinal@0.4.0, tar-fs@0.5.2, bower-
registry-client@0.2.4,
decompress-zip@0.0.8, handlebars@2.0.0, mout@0.9.1, inquirer@0.7.1, insight@0.4.
            3, update-notifier@0.2.0)
└── npm@2.7.6


Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ git clone https://github.com/adaptlearning/adapt_authoring.git
Cloning into 'adapt_authoring'...
remote: Counting objects: 18179, done.
remote: Total 18179 (delta 0), reused 0 (delta 0), pack-reused 18179
Receiving objects: 100% (18179/18179), 41.69 MiB | 4.29 MiB/s, done.
Resolving deltas: 100% (10583/10583), done.
Checking connectivity... done.


Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ npm install


> kerberos@0.0.18 install C:\adapt\Simons Adapt\node_modules\mongodb\node_module
                                s\kerberos

> (node-gyp rebuild) || (exit 0)



C:\adapt\Simons Adapt\node_modules\mongodb\node_modules\kerberos>node "C:\Progra
                                m Files\nodejs\node_modules\npm\bin
\node-gyp-bin\\..\..\node_modules\node-gyp\bi
            n\node-gyp.js" rebuild
gyp
```

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ node install

module.js:340
    throw err;
        ^
Error: Cannot find module 'C:\adapt\Simons Adapt\install'
    at Function.Module._resolveFilename (module.js:338:15)
    at Function.Module._load (module.js:280:25)
    at Function.Module.runMain (module.js:497:10)
    at startup (node.js:119:16)
    at node.js:906:3

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt
$ cd adapt_authoring

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt/adapt_authoring (master)
$ npm install
npm WARN deprecated URIjs@1.12.1: package renamed to "urijs" (lower-case), please update accordingly
npm WARN deprecated lodash@0.9.2: lodash@<2.0.0 is no longer maintained. Upgrade to lodash@^3.0.0
npm WARN deprecated win-spawn@2.0.0: use [cross-spawn](https://github.com/IndigoUnited/node-cross-spawn) or [cross-spawn-async](https://github.com/IndigoUnited/node-cross-spawn-async) instead.
npm WARN deprecated lodash@1.0.2: lodash@<2.0.0 is no longer maintained. Upgrade to lodash@^3.0.0
npm WARN deprecated npmconf@2.1.1: this package has been reintegrated into npm and is now out of date with respect to npm
npm WARN engine boom@2.10.1: wanted: {"node":">=0.10.40"} (current: {"node":"0.10.33","npm":"1.4.28"})
npm WARN engine cryptiles@2.0.5: wanted: {"node":">=0.10.40"} (current: {"node":"0.10.33","npm":"1.4.28"})
npm WARN engine hoek@2.16.3: wanted: {"node":">=0.10.40"} (current: {"node":"0.10.33","npm":"1.4.28"})

> phantomjs@1.9.19 install C:\adapt\Simons Adapt\adapt_authoring\node_modules\grunt-casperjs\node_modules\phantomjs
> node install.js

PhantomJS not found on PATH
Download already available at C:\Users\Simon\AppData\Local\Temp\phantomjs\phantomjs-1.9.8-windows.zip
Verified checksum of previously downloaded file
Extracting zip contents
Removing C:\adapt\Simons Adapt\adapt_authoring\node_modules\grunt-casperjs\node_modules\phantomjs\lib\phantom
Copying extracted folder C:\Users\Simon\AppData\Local\Temp\phantomjs\phantomjs-1.9.8-windows.zip-extract-1454565096292\phantomjs-1.9.8-windows -> C:\adapt\Simons Adapt\adapt_authoring\node_modules\grunt-casperjs\node_modules\phantomjs\lib\phantom
Writing location.js file

> weak@1.0.1 install C:\adapt\Simons Adapt\adapt_authoring\node_modules\phantom\node_modules\dnode\node_modules\weak
> node-gyp rebuild

C:\adapt\Simons Adapt\adapt_authoring\node_modules\phantom\node_modules\dnode
\node_modules\weak>node "C:\Program Files\nodejs\node_modules\npm\bin\node-gyp-bin\\..\..
\node_modules\node-gyp\bin\node-gyp.js" rebuild
gypnpm
> kerberos@0.0.11 install C:\adapt\Simons Adapt\adapt_authoring\node_modules\connect-mongo
\node_modules\mongodb\node_modules\kerberos
> (node-gyp rebuild 2> builderror.log) || (exit 0)

 WARN optional dep failed, continuing weak@1.0.1

C:\adapt\Simons Adapt\adapt_authoring\node_modules\connect-mongo\node_modules\mongodb
\node_modules\kerberos>node "C:\Program Files\nodejs\node_modules\npm\bin\node-gyp-bin\\..\..
\node_modules\node-gyp\bin\node-gyp.js" rebuild

> bson@0.2.22 install C:\adapt\Simons Adapt\adapt_authoring\node_modules\connect-mongo
\node_modules\mongodb\node_modules\bson
> (node-gyp rebuild 2> builderror.log) || (exit 0)

C:\adapt\Simons Adapt\adapt_authoring\node_modules\connect-mongo\node_modules\mongodb
\node_modules\bson>node "C:\Program Files\nodejs\node_modules\npm\bin\node-gyp-bin\\..\..
\node_modules\node-gyp\bin\node-gyp.js" rebuild

> kerberos@0.0.18 install C:\adapt\Simons Adapt\adapt_authoring\node_modules\mongoose
\node_modules\mongodb\node_modules\kerberos
> (node-gyp rebuild) || (exit 0)

C:\adapt\Simons Adapt\adapt_authoring\node_modules\mongoose\node_modules\mongodb
\node_modules\kerberos>node "C:\Program Files\nodejs\node_modules\npm\bin\node-gyp-bin\\..\..
\node_modules\node-gyp\bin\node-gyp.js" rebuild
gypshould@1.3.0 node_modules\should

handlebars-form-helpers@0.1.3 node_modules\handlebars-form-helpers

consolidate@0.10.0 node_modules\consolidate

node-ffprobe@1.2.2 node_modules\node-ffprobe

rimraf@2.2.8 node_modules\rimraf

cookie-parser@1.4.1 node_modules\cookie-parser
├── cookie-signature@1.0.6
└── cookie@0.2.3

bcrypt-nodejs@0.0.3 node_modules\bcrypt-nodejs

underscore@1.5.2 node_modules\underscore

ncp@0.5.1 node_modules\ncp

mkdirp@0.3.5 node_modules\mkdirp

formidable@1.0.17 node_modules\formidable

grunt-concurrent@0.3.1 node_modules\grunt-concurrent
└── lpad@0.1.0

mime@1.2.11 node_modules\mime

async@0.2.5 node_modules\async

semver@5.1.0 node_modules\semver

chalk@1.1.1 node_modules\chalk
├── escape-string-regexp@1.0.4
├── supports-color@2.0.0
├── ansi-styles@2.1.0
├── strip-ansi@3.0.0 (ansi-regex@2.0.0)
└── has-ansi@2.0.0 (ansi-regex@2.0.0)

grunt-contrib-copy@0.4.1 node_modules\grunt-contrib-copy

node-polyglot@0.4.5 node_modules\node-polyglot

validator@4.2.1 node_modules\validator

fs-extra@0.16.5 node_modules\fs-extra
├── jsonfile@2.2.3
└── graceful-fs@3.0.8

grunt-open@0.2.3 node_modules\grunt-open
└── open@0.0.5

serve-favicon@2.3.0 node_modules\serve-favicon
├── fresh@0.3.0
├── ms@0.7.1
├── etag@1.7.0
└── parseurl@1.3.1

jshint-stylish@2.1.0 node_modules\jshint-stylish
├── log-symbols@1.0.2
├── text-table@0.2.0
├── plur@2.1.2 (irregular-plurals@1.1.0)
└── string-length@1.0.1 (strip-ansi@3.0.0)

passport@0.1.18 node_modules\passport
├── pause@0.0.1
└── pkginfo@0.2.3

optimist@0.6.1 node_modules\optimist
├── wordwrap@0.0.3
└── minimist@0.0.10

json-schema-mapper@0.0.2 node_modules\json-schema-mapper
├── underscore@1.6.0
└── URIjs@1.12.1

grunt-mocha-test@0.7.0 node_modules\grunt-mocha-test

morgan@1.6.1 node_modules\morgan

```
├── basic-auth@1.0.3
├── depd@1.0.1
├── on-headers@1.0.1
├── on-finished@2.3.0 (ee-first@1.1.1)
└── debug@2.2.0 (ms@0.7.1)

grunt-bower-requirejs@0.7.1 node_modules\grunt-bower-requirejs
├── slash@0.1.3
└── requirejs@2.1.22

fluent-ffmpeg@1.7.1 node_modules\fluent-ffmpeg
├── exec-queue@0.0.2
└── async@1.5.2

express-session@1.13.0 node_modules\express-session
├── cookie-signature@1.0.6
├── utils-merge@1.0.0
├── cookie@0.2.3
├── parseurl@1.3.1
├── on-headers@1.0.1
├── depd@1.1.0
├── crc@3.4.0
├── uid-safe@2.0.0 (base64-url@1.2.1)
└── debug@2.2.0 (ms@0.7.1)

compression@1.6.1 node_modules\compression
├── on-headers@1.0.1
├── vary@1.1.0
├── bytes@2.2.0
├── debug@2.2.0 (ms@0.7.1)
├── compressible@2.0.7 (mime-db@1.21.0)
└── accepts@1.3.1 (negotiator@0.6.0, mime-types@2.1.9)

body-parser@1.14.2 node_modules\body-parser
├── bytes@2.2.0
├── content-type@1.0.1
├── on-finished@2.3.0 (ee-first@1.1.1)
├── debug@2.2.0 (ms@0.7.1)
├── depd@1.1.0
├── raw-body@2.1.5 (unpipe@1.0.0)
├── qs@5.2.0
├── type-is@1.6.11 (media-typer@0.3.0, mime-types@2.1.9)
├── http-errors@1.3.1 (statuses@1.2.1, inherits@2.0.1)
└── iconv-lite@0.4.13

grunt-contrib-requirejs@0.4.4 node_modules\grunt-contrib-requirejs
└── requirejs@2.1.22

grunt-merge-json@0.9.5 node_modules\grunt-merge-json
├── chalk@0.5.1 (ansi-styles@1.1.0, escape-string-regexp@1.0.4, supports-color@0.2.0, strip-
ansi@0.3.0, has-ansi@0.1.0)
└── lodash@2.4.2

grunt-requirejs-bundle@0.0.9 node_modules\grunt-requirejs-bundle
└── lodash@2.3.0
```

method-override@2.3.5 node_modules\method-override
├── vary@1.0.1
├── methods@1.1.2
├── parseurl@1.3.1
└── debug@2.2.0 (ms@0.7.1)

winston@1.0.2 node_modules\winston
├── cycle@1.0.3
├── stack-trace@0.0.9
├── eyes@0.1.8
├── isstream@0.1.2
├── pkginfo@0.3.1
├── async@1.0.0
└── colors@1.0.3

supertest@0.8.3 node_modules\supertest
├── methods@0.1.0
└── superagent@0.16.0 (methods@0.0.1, debug@0.7.4, qs@0.6.5, cookiejar@1.3.0, emitter-component@1.0.0, mime@1.2.5, reduce-component@1.0.1, formidable@1.0.14)

prompt@0.2.14 node_modules\prompt
├── revalidator@0.1.8
├── read@1.0.7 (mute-stream@0.0.5)
├── pkginfo@0.3.1
├── utile@0.2.1 (deep-equal@1.0.1, async@0.2.10, ncp@0.4.2, i@0.3.4)
└── winston@0.8.3 (cycle@1.0.3, stack-trace@0.0.9, eyes@0.1.8, isstream@0.1.2, colors@0.6.2)

express@4.13.4 node_modules\express
├── escape-html@1.0.3
├── content-type@1.0.1
├── etag@1.7.0
├── array-flatten@1.1.1
├── cookie@0.1.5
├── methods@1.1.2
├── path-to-regexp@0.1.7
├── fresh@0.3.0
├── cookie-signature@1.0.6
├── range-parser@1.0.3
├── vary@1.0.1
├── merge-descriptors@1.0.1
├── serve-static@1.10.2
├── content-disposition@0.5.1
├── utils-merge@1.0.0
├── depd@1.1.0
├── parseurl@1.3.1
├── on-finished@2.3.0 (ee-first@1.1.1)
├── qs@4.0.0
├── finalhandler@0.4.1 (unpipe@1.0.0)
├── proxy-addr@1.0.10 (forwarded@0.1.0, ipaddr.js@1.0.5)
├── send@0.13.1 (destroy@1.0.4, statuses@1.2.1, ms@0.7.1, mime@1.3.4, http-errors@1.3.1)
├── type-is@1.6.11 (media-typer@0.3.0, mime-types@2.1.9)
├── accepts@1.2.13 (negotiator@0.5.3, mime-types@2.1.9)
└── debug@2.2.0 (ms@0.7.1)

errorhandler@1.4.3 node_modules\errorhandler
├── escape-html@1.0.3

└── accepts@1.3.1 (negotiator@0.6.0, mime-types@2.1.9)

request@2.69.0 node_modules\request
├── forever-agent@0.6.1
├── aws-sign2@0.6.0
├── is-typedarray@1.0.0
├── stringstream@0.0.5
├── caseless@0.11.0
├── tunnel-agent@0.4.2
├── oauth-sign@0.8.1
├── isstream@0.1.2
├── json-stringify-safe@5.0.1
├── extend@3.0.0
├── node-uuid@1.4.7
├── combined-stream@1.0.5 (delayed-stream@1.0.0)
├── qs@6.0.2
├── tough-cookie@2.2.1
├── aws4@1.2.1 (lru-cache@2.7.3)
├── form-data@1.0.0-rc3 (async@1.5.2)
├── mime-types@2.1.9 (mime-db@1.21.0)
├── hawk@3.1.3 (cryptiles@2.0.5, sntp@1.0.9, boom@2.10.1, hoek@2.16.3)
├── http-signature@1.1.1 (assert-plus@0.2.0, jsprim@1.2.2, sshpk@1.7.3)
├── har-validator@2.0.6 (pinkie-promise@2.0.0, commander@2.9.0, is-my-json-valid@2.12.4)
└── bl@1.0.2 (readable-stream@2.0.5)

multer@1.1.0 node_modules\multer
├── object-assign@3.0.0
├── xtend@4.0.1
├── append-field@0.1.0
├── on-finished@2.3.0 (ee-first@1.1.1)
├── mkdirp@0.5.1 (minimist@0.0.8)
├── concat-stream@1.5.1 (typedarray@0.0.6, inherits@2.0.1, readable-stream@2.0.5)
├── type-is@1.6.11 (media-typer@0.3.0, mime-types@2.1.9)
└── busboy@0.2.12 (readable-stream@1.1.13, dicer@0.2.5)

mocha@1.13.0 node_modules\mocha
├── growl@1.7.0
├── diff@1.0.7
├── commander@0.6.1
├── debug@2.2.0 (ms@0.7.1)
├── glob@3.2.3 (graceful-fs@2.0.3, inherits@2.0.1, minimatch@0.2.14)
└── jade@0.26.3 (mkdirp@0.3.0)

unzip@0.1.8 node_modules\unzip
├── setimmediate@1.0.4
├── pullstream@0.4.1 (slice-stream@1.0.0, over@0.0.5)
├── match-stream@0.0.2 (buffers@0.1.1)
├── readable-stream@1.0.33 (inherits@2.0.1, string_decoder@0.10.31, isarray@0.0.1, core-util-is@1.0.2)
├── binary@0.3.0 (buffers@0.1.1, chainsaw@0.1.0)
└── fstream@0.1.31 (graceful-fs@3.0.8, mkdirp@0.5.1, inherits@2.0.1)

grunt-contrib-watch@0.5.3 node_modules\grunt-contrib-watch
├── tiny-lr@0.0.4 (debug@0.7.4, qs@0.5.6, faye-websocket@0.4.4, noptify@0.0.3)
└── gaze@0.4.3 (globule@0.1.0)

grunt-contrib-connect@0.11.2 node_modules\grunt-contrib-connect
├── connect-livereload@0.5.4
├── opn@1.0.2
├── async@0.9.2
├── portscanner@1.0.0 (async@0.1.15)
├── serve-static@1.10.2 (escape-html@1.0.3, parseurl@1.3.1, send@0.13.1)
├── connect@3.4.1 (utils-merge@1.0.0, parseurl@1.3.1, finalhandler@0.4.1, debug@2.2.0)
└── serve-index@1.7.3 (escape-html@1.0.3, parseurl@1.3.1, batch@0.5.3, accepts@1.2.13,
mime-types@2.1.9, http-errors@1.3.1, debug@2.2.0)

nodemailer@1.3.4 node_modules\nodemailer
├── nodemailer-direct-transport@1.1.0 (smtp-connection@1.3.8)
├── buildmail@1.3.0 (addressparser@0.3.2, libbase64@0.1.0, libqp@1.1.0)
├── nodemailer-smtp-transport@1.1.0 (nodemailer-wellknown@0.1.7, clone@1.0.2, smtp-
connection@1.3.8)
├── libmime@1.2.0 (libbase64@0.1.0, libqp@1.1.0, iconv-lite@0.4.13)
└── hyperquest@1.2.0 (duplexer2@0.0.2, through2@0.6.5)

needle@0.10.0 node_modules\needle
├── debug@2.2.0 (ms@0.7.1)
└── iconv-lite@0.4.13

matchdep@0.3.0 node_modules\matchdep
├── stack-trace@0.0.7
├── resolve@0.5.1
├── globule@0.1.0 (minimatch@0.2.14, glob@3.1.21, lodash@1.0.2)
└── findup-sync@0.1.3 (glob@3.2.11, lodash@2.4.2)

moment@2.11.2 node_modules\moment

hbs@2.4.0 node_modules\hbs
├── walk@2.2.1 (forEachAsync@2.2.1)
└── handlebars@1.0.12 (optimist@0.3.7, uglify-js@2.3.6)

grunt@0.4.5 node_modules\grunt
├── which@1.0.9
├── dateformat@1.0.2-1.2.3
├── eventemitter2@0.4.14
├── getobject@0.1.0
├── colors@0.6.2
├── async@0.1.22
├── grunt-legacy-util@0.2.0
├── hooker@0.2.3
├── exit@0.1.2
├── nopt@1.0.10 (abbrev@1.0.7)
├── lodash@0.9.2
├── coffee-script@1.3.3
├── iconv-lite@0.2.11
├── underscore.string@2.2.1
├── glob@3.1.21 (inherits@1.0.2, graceful-fs@1.2.3)
├── minimatch@0.2.14 (sigmund@1.0.1, lru-cache@2.7.3)
├── grunt-legacy-log@0.1.3 (grunt-legacy-log-utils@0.1.1, underscore.string@2.3.3, lodash@2.4.2)
├── js-yaml@2.0.5 (esprima@1.0.4, argparse@0.1.16)
└── findup-sync@0.1.3 (glob@3.2.11, lodash@2.4.2)

grunt-contrib-handlebars@0.7.0 node_modules\grunt-contrib-handlebars

```
├── chalk@0.4.0 (has-color@0.1.7, ansi-styles@1.0.0, strip-ansi@0.1.1)
├── grunt-lib-contrib@0.5.3 (zlib-browserify@0.0.1)
└── handlebars@1.3.0 (optimist@0.3.7, uglify-js@2.3.6)

phantom@0.6.6 node_modules\phantom
├── win-spawn@2.0.0
├── traverse@0.6.6
├── shoe@0.0.15 (sockjs@0.3.7)
└── dnode@1.2.2 (jsonify@0.0.0, dnode-protocol@0.2.2)

grunt-casperjs@2.1.0 node_modules\grunt-casperjs
├── phantomjs@1.9.19 (which@1.0.9, progress@1.1.8, kew@0.4.0, request-progress@0.3.1, md5
@2.0.0, adm-zip@0.4.4, fs-extra@0.23.1, request@2.42.0, npmconf@2.1.1)
└── casperjs@1.1.0-beta3

connect-mongo@0.4.2 node_modules\connect-mongo
└── mongodb@1.4.40 (readable-stream@2.0.5, kerberos@0.0.11, bson@0.2.22)

grunt-contrib-jshint@0.11.3 node_modules\grunt-contrib-jshint
├── hooker@0.2.3
└── jshint@2.8.0 (strip-json-comments@1.0.4, exit@0.1.2, console-browserify@1.1.0, minimatch@
2.0.10, shelljs@0.3.0, cli@0.6.6, htmlparser2@3.8.3, lodash@3.7.0)

grunt-contrib-less@0.7.0 node_modules\grunt-contrib-less
├── grunt-lib-contrib@0.6.1 (zlib-browserify@0.0.1)
└── less@1.4.2 (ycssmin@1.0.1)

node-gyp@3.1.0 node_modules\node-gyp
├── graceful-fs@4.1.3
├── nopt@3.0.6 (abbrev@1.0.7)
├── osenv@0.1.3 (os-homedir@1.0.1, os-tmpdir@1.0.1)
├── minimatch@1.0.0 (sigmund@1.0.1, lru-cache@2.7.3)
├── fstream@1.0.8 (inherits@2.0.1)
├── mkdirp@0.5.1 (minimist@0.0.8)
├── which@1.2.4 (isexe@1.1.1, is-absolute@0.1.7)
├── glob@4.5.3 (inherits@2.0.1, inflight@1.0.4, minimatch@2.0.10, once@1.3.3)
├── tar@2.2.1 (inherits@2.0.1, block-stream@0.0.8)
├── npmlog@1.2.1 (ansi@0.3.1, are-we-there-yet@1.0.6, gauge@1.2.5)
└── path-array@1.0.1 (array-index@1.0.0)

mongoose@4.2.6 node_modules\mongoose
├── ms@0.7.1
├── mpath@0.1.1
├── async@0.9.0
├── regexp-clone@0.0.1
├── hooks-fixed@1.1.0
├── kareem@1.0.1
├── muri@1.0.0
├── sliced@0.0.5
├── mpromise@0.5.4
├── bson@0.4.21
├── mquery@1.6.3 (debug@2.2.0, bluebird@2.9.26)
└── mongodb@2.0.48 (readable-stream@1.0.31, es6-promise@2.1.1, kerberos@0.0.18, mongodb-
core@1.2.21)

archiver@0.16.0 node_modules\archiver
```

```
├── buffer-crc32@0.2.5
├── async@1.4.2
├── lazystream@0.1.0
├── readable-stream@1.0.33 (isarray@0.0.1, string_decoder@0.10.31, core-util-is@1.0.2,
inherits@2.0.1)
├── zip-stream@0.6.0 (compress-commons@0.3.0)
├── glob@5.0.15 (path-is-absolute@1.0.0, inherits@2.0.1, inflight@1.0.4, once@1.3.3, minimatch@
3.0.0)
├── tar-stream@1.2.2 (bl@1.0.2, xtend@4.0.1, end-of-stream@1.1.0, readable-stream@2.0.5)
└── lodash@3.10.1

grunt-jscs@2.7.0 node_modules\grunt-jscs
├── vow@0.4.12
├── hooker@0.2.3
├── lodash@3.10.1
└── jscs@2.9.0 (strip-json-comments@1.0.4, estraverse@4.1.1, exit@0.1.2, commander@2.9.0,
esprima@2.7.2, to-single-quotes@2.0.0, natural-compare@1.2.2, pathval@0.1.1, to-double-
quotes@2.0.0, reserved-words@0.1.1, jscs-preset-wikimedia@1.0.0, cli-table@0.3.1, xmlbuilder@
3.1.0, resolve@1.1.7, minimatch@3.0.0, glob@5.0.15, strip-bom@2.0.0, vow-fs@0.3.4, jscs-jsdoc@
1.3.1, htmlparser2@3.8.3, jsonlint@1.6.2, escope@3.4.0, js-yaml@3.4.6, babel-jscs@2.0.5)

bower@1.6.5 node_modules\bower
```

Simon@simons-lappie MINGW64 /c/adapt/Simons Adapt/adapt_authoring (master)
$ node install
This script will install the Adapt Builder. Would you like to continue?
> Y/n (Y)
The Adapt Framework was not found. It will now be installed...
 Cloning into 'adapt_framework'...

Clone from GitHub was successful.
Running 'npm install' for the Adapt Framework...
 npm

 WARN

 deprecated
 lodash@0.9.2: lodash@<2.0.0 is no longer maintained. Upgrade to lodash@^3.0.0

 npm

 WARN

 deprecated
 lodash@1.0.2: lodash@<2.0.0 is no longer maintained. Upgrade to lodash@^3.0.0

 npm

 WARN

 engine
 deep-extend@0.4.1: wanted: {"node":">=0.12.0","iojs":">=1.0.0"} (current:
{"node":"0.10.33","npm":"1.4.28"})

 npm

underscore-deep-extend@0.0.5 node_modules\underscore-deep-extend

adapt-grunt-tracking-ids@0.1.2 node_modules\adapt-grunt-tracking-ids

underscore@1.6.0 node_modules\underscore

grunt-contrib-clean@0.6.0 node_modules\grunt-contrib-clean
└── rimraf@2.2.8

chalk@1.1.1 node_modules\chalk
├── supports-color@2.0.0
├── escape-string-regexp@1.0.4
├── ansi-styles@2.1.0
├── strip-ansi@3.0.0 (ansi-regex@2.0.0)
└── has-ansi@2.0.0 (ansi-regex@2.0.0)

grunt-open@0.2.3 node_modules\grunt-open
└── open@0.0.5

grunt-contrib-copy@0.6.0 node_modules\grunt-contrib-copy
└── chalk@0.5.1 (ansi-styles@1.1.0, supports-color@0.2.0, escape-string-regexp@1.0.4, has-ansi@0.1.0, strip-ansi@0.3.0)

grunt-concurrent@1.0.1 node_modules\grunt-concurrent
├── pad-stdio@1.0.0 (lpad@1.0.0)
└── async@0.9.2

columnify@1.5.4 node_modules\columnify
├── strip-ansi@3.0.0 (ansi-regex@2.0.0)

└── wcwidth@1.0.0 (defaults@1.0.3)

grunt-contrib-concat@0.5.1 node_modules\grunt-contrib-concat
├── chalk@0.5.1 (ansi-styles@1.1.0, escape-string-regexp@1.0.4, supports-color@0.2.0, strip-ansi@0.3.0, has-ansi@0.1.0)
└── source-map@0.3.0 (amdefine@1.0.0)

grunt-contrib-requirejs@0.4.4 node_modules\grunt-contrib-requirejs
└── requirejs@2.1.22

lodash@2.4.2 node_modules\lodash

matchdep@0.3.0 node_modules\matchdep
├── stack-trace@0.0.7
├── resolve@0.5.1
├── findup-sync@0.1.3 (glob@3.2.11)
└── globule@0.1.0 (minimatch@0.2.14, glob@3.1.21, lodash@1.0.2)

grunt-requirejs-bundle@0.0.9 node_modules\grunt-requirejs-bundle
└── lodash@2.3.0

grunt-contrib-watch@0.6.1 node_modules\grunt-contrib-watch
├── async@0.2.10
├── tiny-lr-fork@0.0.5 (debug@0.7.4, faye-websocket@0.4.4, qs@0.5.6, noptify@0.0.3)
└── gaze@0.5.2 (globule@0.1.0)

grunt@0.4.5 node_modules\grunt
├── eventemitter2@0.4.14
├── which@1.0.9
├── dateformat@1.0.2-1.2.3
├── getobject@0.1.0
├── rimraf@2.2.8
├── colors@0.6.2
├── async@0.1.22
├── grunt-legacy-util@0.2.0
├── hooker@0.2.3
├── exit@0.1.2
├── nopt@1.0.10 (abbrev@1.0.7)
├── glob@3.1.21 (inherits@1.0.2, graceful-fs@1.2.3)
├── minimatch@0.2.14 (sigmund@1.0.1, lru-cache@2.7.3)
├── lodash@0.9.2
├── coffee-script@1.3.3
├── underscore.string@2.2.1
├── iconv-lite@0.2.11
├── js-yaml@2.0.5 (esprima@1.0.4, argparse@0.1.16)
├── findup-sync@0.1.3 (glob@3.2.11, lodash@2.4.2)
└── grunt-legacy-log@0.1.3 (grunt-legacy-log-utils@0.1.1, underscore.string@2.3.3, lodash@2.4.2)

grunt-contrib-connect@0.8.0 node_modules\grunt-contrib-connect
├── connect-livereload@0.4.1
├── open@0.0.5
├── async@0.9.2
├── portscanner@0.2.3 (async@0.1.15)
└── connect@2.19.6 (qs@0.6.6, escape-html@1.0.1, bytes@1.0.0, cookie@0.1.2, errorhandler@1.0.2, pause@0.0.1, parseurl@1.0.1, fresh@0.2.2, basic-auth-connect@1.0.0, on-headers@0.0.0, cookie-sig

nature@1.0.3, morgan@1.1.1, response-time@2.0.0, vhost@1.0.0, serve-favicon@2.0.1, debug@1.0.2, cookie-parser@1.1.0, body-parser@1.3.1, connect-timeout@1.1.0, method-override@2.0.2, type-is@1.
2.1, compression@1.0.7, express-session@1.2.1, multiparty@3.2.8, csurf@1.2.1, serve-static@1.2.3, serve-index@1.1.1)

grunt-jsonlint@1.0.7 node_modules\grunt-jsonlint
├── strip-json-comments@2.0.0
└── jsonlint@1.6.2 (nomnom@1.8.1, JSV@4.0.2)

grunt-contrib-handlebars@0.9.3 node_modules\grunt-contrib-handlebars
├── nsdeclare@0.1.0
├── chalk@0.4.0 (has-color@0.1.7, ansi-styles@1.0.0, strip-ansi@0.1.1)
└── handlebars@2.0.0 (optimist@0.3.7, uglify-js@2.3.6)

assemble-less@0.7.0 node_modules\assemble-less
├── async@0.2.10
├── grunt-lib-contrib@0.6.1 (zlib-browserify@0.0.1)
└── less@1.6.3 (mime@1.2.11, mkdirp@0.3.5, source-map@0.1.43, clean-css@2.0.8, request@2.69.0)

grunt-bower-requirejs@1.1.1 node_modules\grunt-bower-requirejs
└── bower-requirejs@1.2.0 (slash@1.0.0, object-assign@2.1.1, sudo-block@1.2.0, nopt@3.0.6, requirejs@2.1.22, file-utils@0.2.2, lodash@3.10.1, update-notifier@0.3.2)

grunt-contrib-less@0.11.4 node_modules\grunt-contrib-less
├── async@0.2.10
├── chalk@0.5.1 (ansi-styles@1.1.0, escape-string-regexp@1.0.4, supports-color@0.2.0, has-ansi@0.1.0, strip-ansi@0.3.0)
├── maxmin@0.1.0 (pretty-bytes@0.1.2, chalk@0.4.0, gzip-size@0.1.1)
└── less@1.7.5 (mime@1.2.11, graceful-fs@3.0.8, source-map@0.1.43, clean-css@2.2.23, mkdirp@0.5.1, request@2.40.0)

bower@1.3.12 node_modules\bower
├── is-root@1.0.0
├── which@1.0.9
├── chmodr@0.1.0
├── abbrev@1.0.7
├── archy@0.0.2
├── bower-logger@0.2.2
├── rimraf@2.2.8
├── junk@1.0.2
├── bower-endpoint-parser@0.2.2
├── stringify-object@1.0.1
├── lru-cache@2.5.2
├── nopt@3.0.6
├── osenv@0.1.0
├── retry@0.6.0
├── opn@1.0.2
├── lockfile@1.0.1
├── graceful-fs@3.0.8
├── q@1.0.1
├── tmp@0.0.23
├── request-progress@0.3.0 (throttleit@0.0.2)
├── semver@2.3.2
├── chalk@0.5.0 (ansi-styles@1.1.0, escape-string-regexp@1.0.4, supports-color@0.2.0, strip-

ansi@0.3.0, has-ansi@0.1.0)
├── shell-quote@1.4.3 (array-filter@0.0.1, array-map@0.0.0, array-reduce@0.0.0, jsonify@0.0.0)
├── promptly@0.2.0 (read@1.0.7)
├── mkdirp@0.5.0 (minimist@0.0.8)
├── p-throttler@0.1.0 (q@0.9.7)
├── bower-json@0.4.0 (intersect@0.0.3, deep-extend@0.2.11, graceful-fs@2.0.3)
├── fstream@1.0.8 (graceful-fs@4.1.3, inherits@2.0.1)
├── fstream-ignore@1.0.3 (inherits@2.0.1, minimatch@3.0.0)
├── glob@4.0.6 (inherits@2.0.1, once@1.3.3, minimatch@1.0.0)
├── bower-config@0.5.2 (osenv@0.0.3, graceful-fs@2.0.3, optimist@0.6.1)
├── tar-fs@0.5.2 (pump@0.3.5, tar-stream@0.4.7)
├── decompress-zip@0.0.8 (nopt@2.2.1, mkpath@0.1.0, touch@0.0.2, readable-stream@1.1.13, binary@0.3.0)
├── cardinal@0.4.0 (redeyed@0.4.4)
├── request@2.42.0 (aws-sign2@0.5.0, forever-agent@0.5.2, caseless@0.6.0, tunnel-agent@0.4.2, oauth-sign@0.4.0, stringstream@0.0.5, json-stringify-safe@5.0.1, mime-types@1.0.2, qs@1.2.2, node-uuid@1.4.7, tough-cookie@2.2.1, http-signature@0.10.1, form-data@0.1.4, bl@0.9.5, hawk@1.1.1)
├── bower-registry-client@0.2.4 (request-replay@0.2.0, graceful-fs@2.0.3, lru-cache@2.3.1, async@0.2.10, mkdirp@0.3.5, request@2.51.0)
├── mout@0.9.1
├── handlebars@2.0.0 (optimist@0.3.7, uglify-js@2.3.6)
├── inquirer@0.7.1 (figures@1.4.0, mute-stream@0.0.4, through@2.3.8, readline2@0.1.1, cli-color@0.3.3, rx@2.5.3)
├── insight@0.4.3 (object-assign@1.0.0, async@0.9.2, chalk@0.5.1, lodash.debounce@2.4.1, os-name@1.0.3, tough-cookie@0.12.1, inquirer@0.6.0, configstore@0.3.2)
└── update-notifier@0.2.0 (semver-diff@0.1.0, string-length@0.1.2, latest-version@0.2.0, configstore@0.3.2)

Completed installing NodeJS modules.

You will now be prompted to set configuration items. Just press ENTER to accept the default value (in brackets).
> Server port (5000)
> Server name (localhost)
> Database host (localhost)
> Master database name (adapt-tenant-master)
> Database server port (27017)
> Data directory path (data)
> Session secret (your-session-secret) faflives1
> Will ffmpeg be used? y/N (N)
> Which SMTP service (if any) will be used? (see https://github.com/andris9/nodemailer-wellknown#supported-services for a list of supported services.) (none)
> SMTP username
> SMTP password
> Sender email address
Checking configuration, please wait a moment ...
You will now be prompted to enter details for your tenant.
> Set a unique name for your tenant (master) localadapt
> Set the display name for your tenant (Master) Adapt Local